


INSULATED BOOTLACE FERRULES FOR DUAL CABLES

3009.0

HZL 1.0, 1.0 x 8mm, Dual Ferrule, Yellow

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Cross section max	1 mm ²
Rated wire cross section to (AWG)	17
Standard	German Standard

DIMENSIONS

Length	15 mm
Length of tube	8 mm
Stripping length	12 mm
Thickness of collar	0.3 mm
Thickness of tube	0.15 mm
Diameter of tube	2 mm

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.25 g
Pack size	500

