


## SPECIAL INSULATED FERRULES

3081.0

H2.5/14-D SR, 2.5 x 14mm Compact Ferrule, Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simple distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated

## TECHNICAL DATA

### GENERAL DATA

Colour	Blue
Cross section max	2.5 mm <sup>2</sup>
Rated wire cross section to (AWG)	14

### DIMENSIONS

Length	14 mm
Stripping length	8 mm

### MATERIALS

Contact surface	Galvanic tin-plated, shiny
Operating temperature from	-5 °C

Operating temperature to	105 °C
--------------------------	--------

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.15 g
Pack size	500
Plastic collar	Polypropylene-homopolymer
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Standard	German/UL (DIN) Standard
Conductor tube	Copper alloy
Diameter of collar	4 mm
Diameter of tube	2.2 mm
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length of tube	8 mm

