

INSULATED BOOTLACE FERRULES FOR DUAL CABLES

3023.0

HZL 10.0 L, 10.0 x 30mm, Dual Ferrule, Ivory

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

TECHNICAL DATA

GENERAL DATA

Colour	Ivory
Cross section max	10 mm ²
Rated wire cross section to (AWG)	8
Standard	German Standard

DIMENSIONS

Length	30 mm
Length of tube	18 mm
Stripping length	23 mm
Thickness of collar	0.5 mm
Thickness of tube	0.2 mm
Diameter of tube	5.8 mm

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.22 g
Pack size	100

