
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SPECIAL INSULATED FERRULES

3079.0
H 1.0/14 7 AWG x 14mm Ferrule, Yellow

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simple distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Cross section max	1 mm²
Rated wire cross section to (AWG)	17

DIMENSIONS

Length	14 mm
Stripping length	10 mm

MATERIALS

Contact surface	Galvanic tin-plated, shiny
Operating temperature from	-5 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0.12 g
Pack size	500

Plastic collar	Polypropylene-homopolymer
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Standard	German Standard
Conductor tube	Copper alloy
Diameter of collar	3.5 mm
Diameter of tube	1.4 mm
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length of tube	8 mm

