
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SPECIAL INSULATED FERRULES

3091.0
H 0.75/14-D, 18 AWG x 14mm Ferrule, Grey

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simple distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

TECHNICAL DATA

GENERAL DATA

Colour	Grey
Cross section max	0.75 mm²
Rated wire cross section to (AWG)	18

DIMENSIONS

Length	14 mm
Stripping length	10 mm

MATERIALS

Contact surface	Galvanic tin-plated, shiny
Operating temperature from	-5 °C
Operating temperature to	105 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.11 g
Pack size	500

Plastic collar	Polypropylene-homopolymer
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Standard	UL (DIN) Standard
Conductor tube	Copper alloy
Diameter of collar	3.4 mm
Diameter of tube	1.2 mm
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length of tube	8 mm

