

### OEM Automatic Ltd


Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



### **SPECIAL INSULATED FERRULES**

3092.0 H 1.0/14-D, 17 AWG x 14mm Ferrule, Red

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simple distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Funnel feed-in made of polypropylene
- $\bullet$  Heat resistant up to 120  $^{\circ}\text{C}$
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

## **TECHNICAL DATA**

## **GENERAL DATA**

Colour	Red
Cross section max	1 mm²
Rated wire cross section to (AWG)	17
Standard	UL (DIN)/French Standard
DIMENSIONS	

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm

Thickness of tube	0.15 mm
Diameter of collar	3.5 mm
Diameter of tube	1.4 mm

# **MATERIALS**

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

# **APPROVALS**

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

# **ADDITIONAL DATA**

Tariff code	85369010
Country of origin	EEC
Weight	0.12 g
Pack size	500



