


## INSULATED BOOTLACE FERRULES 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30MA000312

0.34mm<sup>2</sup> x 6mm ferrule on Reel - Cyan

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

## TECHNICAL DATA

### GENERAL DATA

Colour	Turquoise
Cross section max	0,34 mm <sup>2</sup>
Rated wire cross section to (AWG)	22
Standard	German Standard

### DIMENSIONS

Length	10 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0,25 mm
Thickness of tube	0,15 mm
Diameter of collar	2 mm

Diameter of tube	0,85 mm
------------------	---------

### MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0,06 g
Pack size	5000

