


**INSULATED BOOTLACE FERRULES**  
**0.14MM<sup>2</sup> TO 4MM<sup>2</sup>**

V30AE001669

0.14mm<sup>2</sup> x 6mm Ferrule - Brown

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION**

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

**TECHNICAL DATA****GENERAL DATA**

<b>Colour</b>	Brown
<b>Cross section max</b>	0.14 mm <sup>2</sup>
<b>Rated wire cross section to (AWG)</b>	26
<b>Standard</b>	French Standard

**DIMENSIONS**

<b>Length</b>	10 mm
<b>Length of tube</b>	6 mm
<b>Stripping length</b>	8 mm
<b>Thickness of collar</b>	0.25 mm
<b>Thickness of tube</b>	0.15 mm
<b>Diameter of collar</b>	1.8 mm

Diameter of tube 0.85 mm

**MATERIALS**

Conductor tube Copper alloy

Contact surface Galvanic tin-plated, shiny

Plastic collar Polypropylene-homopolymer

Operating temperature from -5 °C

Operating temperature to 105 °C

**APPROVALS**

DIN 46228-4:1990 Yes

DIN 46228-1:1992 No



**ADDITIONAL DATA**

Tariff code 85369010

Country of origin DE

Weight 0.06 g

Pack size 500



Bezeichnung Description		AWG	Pitchcode/Serial-Nr. Color code/Order no.		Nennmaße mm Dimensions mm					Stück Pieces			
AWG	L <sub>1</sub>	Typ Type	ZiF	DN	KDS	L <sub>1</sub>	L <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	VPE			
0.14	8	N	26	V30AE029507	V30AE029509	10	8	0.8	0.15	1.5	0.25	500	
0.14	8	L	26	V30AE029508	V30AE029510	10	8	0.8	0.15	1.5	0.25	500	
0.25	8	N	24	V30AE030001	V30AE030002	10	8	0.85	0.15	1.8	0.25	500	
					V30AE030044								
0.25	8	L	24	V30AE030002	V30AE030003	10	8	0.85	0.15	1.8	0.25	500	
					V30AE030083								
					V30AE030045								
0.25	12	LS	24	V30AE034185	V30AE034184	15	12	0.85	0.15	1.8	0.25	500	
					V30AE030004								
0.34	8	N	22	V30AE030003	V30AE030005	10	8	0.85	0.15	2	0.25	500	
					V30AE030085								
0.34	8	L	22	V30AE030004	V30AE030007	10	8	0.85	0.15	2	0.25	500	
					V30AE030087								
0.34	12	LS	22	V30AE034186	V30AE034187	15	12	0.85	0.15	2	0.25	500	
0.5	8	K	20	V30AE030005	V30AE030007	V30AE030007	12	8	1	0.15	2.6	0.25	500
0.5	8	N	20	V30AE030005	V30AE030008	V30AE030008	14	8	1	0.15	2.6	0.25	500
0.8	10	HL	20	V30AE030007	V30AE030009	V30AE030009	16	10	1	0.15	2.6	0.25	500
0.8	12	L	20	V30AE034188	V30AE034189	V30AE034189	15	12	1	0.15	2.6	0.25	500
0.75	8	K	18	V30AE030008	V30AE030040	V30AE030046	12	8	1.2	0.15	2.8	0.25	500
0.75	8	N	18	V30AE030009	V30AE030041	V30AE030048	14	8	1.2	0.15	2.8	0.25	500
0.75	8	HL	18	V30AE030007	V30AE030086	V30AE030088	16	8	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V30AE030010	V30AE030042	V30AE030047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE030011	V30AE030043	V30AE030048	16	12	1.2	0.15	2.8	0.25	500
1	8	K	16	V30AE030012	V30AE030044	V30AE030044	12	8	1.4	0.15	3	0.25	500
1	8	N	16	V30AE030013	V30AE030045	V30AE030045	14	8	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE030014	V30AE030046	V30AE030046	16	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE030015	V30AE030047	V30AE030047	15	12	1.4	0.15	3	0.25	500
1.5	8	K	14	V30AE030704	V30AE030705	V30AE030705	12	8	1.7	0.15	3.5	0.25	500
1.5	8	N	14	V30AE030016	V30AE030048	V30AE030048	14	8	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE030017	V30AE030049	V30AE030049	16	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description		AWG	Pitchcode/Serial-Nr. Color code/Order no.		Nennmaße mm Dimensions mm					Stück Pieces			
AWG	L <sub>1</sub>	Typ Type	ZiF	DN	KDS	L <sub>1</sub>	L <sub>2</sub>	ℓ <sub>1</sub>	ℓ <sub>2</sub>	VPE			
0.14	8	N	26	V30AE029507	V30AE029509	10	8	0.8	0.15	1.5	0.25	500	
0.14	8	L	26	V30AE029508	V30AE029510	10	8	0.8	0.15	1.5	0.25	500	
0.25	8	N	24	V30AE030001	V30AE030002	10	8	0.85	0.15	1.8	0.25	500	
					V30AE030044								
0.25	8	L	24	V30AE030002	V30AE030003	10	8	0.85	0.15	1.8	0.25	500	
					V30AE030083								
					V30AE030045								
0.25	12	LS	24	V30AE034185	V30AE034184	15	12	0.85	0.15	1.8	0.25	500	
					V30AE030004								
0.34	8	N	22	V30AE030003	V30AE030005	V30AE030005	10	8	0.85	0.15	2	0.25	500
					V30AE030085								
0.34	8	L	22	V30AE030004	V30AE030007	V30AE030007	10	8	0.85	0.15	2	0.25	500
					V30AE030087								
0.34	12	LS	22	V30AE034186	V30AE034187	15	12	0.85	0.15	2	0.25	500	
0.5	8	K	20	V30AE030005	V30AE030007	V30AE030007	12	8	1	0.15	2.6	0.25	500
0.5	8	N	20	V30AE030005	V30AE030008	V30AE030008	14	8	1	0.15	2.6	0.25	500
0.8	10	HL	20	V30AE030007	V30AE030009	V30AE030009	16	10	1	0.15	2.6	0.25	500
0.8	12	L	20	V30AE034188	V30AE034189	V30AE034189	15	12	1	0.15	2.6	0.25	500
0.75	8	K	18	V30AE030008	V30AE030040	V30AE030046	12	8	1.2	0.15	2.8	0.25	500
0.75	8	N	18	V30AE030009	V30AE030041	V30AE030048	14	8	1.2	0.15	2.8	0.25	500
0.75	8	HL	18	V30AE030007	V30AE030086	V30AE030088	16	8	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V30AE030010	V30AE030042	V30AE030047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE030011	V30AE030043	V30AE030048	16	12	1.2	0.15	2.8	0.25	500
1	8	K	16	V30AE030012	V30AE030044	V30AE030044	12	8	1.4	0.15	3	0.25	500
1	8	N	16	V30AE030013	V30AE030045	V30AE030045	14	8	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE030014	V30AE030046	V30AE030046	16	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE030015	V30AE030047	V30AE030047	15	12	1.4	0.15	3	0.25	500
1.5	8	K	14	V30AE030704	V30AE030705	V30AE030705	12	8	1.7	0.15	3.5	0.25	500
1.5	8	N	14	V30AE030016	V30AE030048	V30AE030048	14	8	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE030017	V30AE030049	V30AE030049	16	10	1.7	0.15	3.5	0.25	500

