
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000001
0.25mm² x 6mm Ferrule - Light Blue



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14…4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.
The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.
Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Light blue
Cross section max	0.25 mm²
Rated wire cross section to (AWG)	24
Standard	German Standard

DIMENSIONS

Length	12 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	1.8 mm
Diameter of tube	0.85 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.06 g
Pack size	500

