


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **INSULATED BOOTLACE FERRULES** 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>



V30AE001663 0.25mm<sup>2</sup> x 8mm Ferrule - Violet

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



## PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

Euopean manufactured, this range ensures a reliable crimp without splitting.

## **TECHNICAL DATA**

## **GENERAL DATA**

Colour	Violet
Cross section max	0.25 mm <sup>2</sup>
Rated wire cross section to (AWG)	24
Standard	French Standard
DIMENSIONS	
Length	12 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	1.8 mm

Diameter of tube	0.85 mm
MATERIALS	
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C
APPROVALS	
DIN 46228-4:1990	Yes
DIN 46228-1:1992	No
ADDITIONAL DATA	
Tariff code	85369010
Country of origin	DE

	52
Weight	0.07 g
Pack size	500

d<sub>2</sub>





Beenthing aw			ANG Perbook/Setel N. Ouker code/Order No.				Nervingle mm Denervene mm						State Pecce
03/02	$1_{k}$	Typ*		28	ON	K05	$\mathbf{u}_i$	14	(0)	8,	$\langle \sigma_{\mu} \rangle$	$\delta_i$	. vet
0,14	: 6	N	26	V204E009667		VODAECONOSO	:10	. 6.	0.6	0.15	1.5	0.25	500
0.14	0	L.	26	VS0AE001968		V3545001081	12	6	0.0	0.15	1.5	0.25	500
0.25	8	Ņ	24	VISOABIODODI		V004E001082 V004E001044	10		0.85	0.15	1.8	0.29	900
0.55					VXXAE001683								
0.90		赤	24	V30AE000002		V30AE001648	-12	1.4	0.05	0.18	-14	0.26	800
0.15	12	LS	24	VIOAE004155		V30AE004154	-16	.12	0.05	0.15	1.0	0.75	500
					V20AE001084								
0,34	.6	<u>N</u> .	22	V30AE000003		V20AE000535	10		0.65	0,15	2	0.25	509
	54 B L 22				V00A0001666			0.05	0.15		0.25	500	
0,54		22	VGOAE000004		V30AE008677	12	. 1			3			
0.34	-12	LB.	22	V304E004156		V00AE00#187	18	12	0.85	0.15	2	0.25	500
0.5	0	к	20	V30AE000005	V304E000037	V30AE000037	.12	0		0.15	2.6	0.25	500
0.6	1	N	20	VODAE000005	VICAEDOOODB	VODAECOCOOR	.94			0.15	2.0	0.25	500
0.8	13	HL.	20	V304E000007	V3045000039	V304E000039	.45	90		0.15	2.0	0.29	800
0.0	- 12	£.	20	VIOAEDOHISE	VSQAEDOHISB	V30AE004H59	30	12		0,15	2.0	0.25	100
0.75	. 6	ĸ	18.	VIGAE000008	V3042000040	V3042000548	17	-6	12	0.15	2.8	0.25	500
0,75	- 8	Ň	10	V35AE000009	V3042000041	V304E000546	14		4.2	0.15	2,0	0.25	500
0,75	:0	14.5	10	VISAE008087	VIOAROODEBD	VIOADOOOBB	.15	. 9	.62	0.10	-2.0	0,25	000
0.75	-80	HL.	SE.	V30AE000010	V30A8000042	VJDA8000547	50	93	12	0.15	2,8	0.25	500
0.75	12	L.	18	VIOAE00001	V3045000043	V3042000548	55	12	12	0.15	2.8	0.25	500
1	.0	ĸ	18	V3046000012	V3045000044	VODAEDOOD4+	10	- e	1.4	0.15	5	0.25	500
	8	N	10	V30A2000018	V304E000048	V004E000048	34	8	1.4	0.15	3	0.25	500
	.90	HL.	18.	V30AED00014	V3048000048	V304E000048	-18	10	1.4	0.15	10	0.25	800
÷.	-12	L	18.	VSOAE000075	V3046000047	100AE000047	15	12	1.4	0.15	3	0.25	500
13	. a	к	10	V30AD003704	V30AE001705	V30A0001705	12			0.15	2.5	0.25	500
1.5	0	.N	10	V30AE000018	VICADODOD45	V0046000048	.14		1.7	0.16	3,6	0.26	500
1.6	=0	HL.	16	V304E000017	VIDAE0000E9	V3042000049	16	10		0.15	2.5	0.25	500

d, S,