


INSULATED BOOTLACE FERRULES

0.14MM² TO 4MM²

V30AE001645

0.25mm² x 8mm Ferrule - Yellow

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Cross section max	0.25 mm ²
Rated wire cross section to (AWG)	24
Standard	French Standard

DIMENSIONS

Length	12 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	1.8 mm

Diameter of tube	0.85 mm
------------------	---------

MATERIALS


Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS


DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.07 g
Pack size	500



Beschreibung Description	WEG	ZuF	Partikelcode/Symbol code/ID no.	KDS	L ₁	L ₂	L ₃	L ₄	L ₅	L ₆	St. Price
			DN								VPE
0.04	E	N	26	V50A001967	V50A002069	10	8	0.6	0.15	0.15	0.25 500
0.04	E	L	26	V50A001968	V50A002081	12	8	0.6	0.15	0.15	0.25 500
0.04	N	N	24	V50A001988	V50A002082	10	8	0.6	0.15	0.15	0.25 500
0.04	N	N	24	V50A001991	V50A002084	10	8	0.6	0.15	0.15	0.25 500
0.04	N	L	24	V50A001992	V50A001993	12	8	0.6	0.15	0.15	0.25 500
0.04	L	LB	24	V50A001995	V50A001995	10	12	0.6	0.15	0.15	0.25 500
0.04	N	N	22	V50A001999	V50A002094	10	8	0.6	0.15	0.15	0.25 500
0.04	E	S	22	V50A002004	V50A002095	10	8	0.6	0.15	0.15	0.25 500
0.04	E	S	22	V50A002004	V50A002096	12	8	0.6	0.15	0.15	0.25 500
0.04	L	LB	22	V50A002006	V50A002097	10	12	0.6	0.15	0.15	0.25 500
0.04	E	K	20	V50A002006	V50A002097	12	8	1	0.15	0.15	0.25 500
0.04	N	N	20	V50A002006	V50A002098	10	8	1	0.15	0.15	0.25 500
0.04	N	N	20	V50A002007	V50A002099	10	10	1	0.15	0.15	0.25 500
0.04	L	L	20	V50A002018	V50A002099	10	12	1	0.15	0.15	0.25 500
0.75	E	K	N	V50A002009	V50A002040	12	8	12	0.15	0.15	0.25 500
0.75	N	N	N	V50A002009	V50A002041	14	8	12	0.15	0.15	0.25 500
0.75	N	H/LB	N	V50A002007	V50A002086	10	9	12	0.15	0.15	0.25 500
0.75	N	HL	N	V50A002010	V50A002042	10	13	12	0.15	0.15	0.25 500
0.75	N	L	N	V50A002001	V50A002043	10	13	12	0.15	0.15	0.25 500
1	E	K	N	V50A002032	V50A002044	12	8	14	0.15	0.15	0.25 500
1	E	N	N	V50A002033	V50A002045	14	8	14	0.15	0.15	0.25 500
1	E	K	N	V50A002046	V50A002046	10	10	14	0.15	0.15	0.25 500
1	L	L	N	V50A002047	V50A002047	10	12	14	0.15	0.15	0.25 500
1.5	E	K	N	V50A002074	V50A002075	10	17	0.15	0.15	0.15	0.25 500
1.6	N	N	N	V50A002098	V50A002048	14	8	17	0.15	0.15	0.25 500
1.6	L	LB	N	V50A002017	V50A002049	15	17	0.15	0.15	0.15	0.25 500

[illegible]

