

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000038

0.5mm² x 8mm Ferrule - White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	White
Cross section max	0.5 mm ²
Rated wire cross section to (AWG)	20
Standard	UL (DIN)/French Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.6 mm

Diameter of tube	1 mm
------------------	------

MATERIALS



Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.09 g
Pack size	500



Bezeichnung Description	AWG	Part Type	Z-#	Partcode/Serial Colour code/Order no.	DRN	KDS	L ₁	L ₂	d ₁	d ₂	S ₁	S ₂	Stück Pieces
mmF	L ₁	L ₂	Z-#	DRN	KDS	L ₁	L ₂	d ₁	d ₂	S ₁	S ₂	VPE	
0.14	6	N	26	V30AE000907		V30AE000909	10	6	0.6	0.15	1.5	0.25	500
0.14	6	L	26	V30AE000908		V30AE000910	10	6	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000001		V30AE000002	10	6	0.65	0.16	1.8	0.29	500
						V30AE000044							
0.25	6	L	24	V30AE000002		V30AE000003	10	6	0.65	0.16	1.8	0.29	500
						V30AE000045							
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.65	0.15	1.8	0.25	500
						V30AE000004							
0.34	6	N	22	V30AE000003		V30AE000005	10	6	0.65	0.16	2	0.29	500
						V30AE000006							
0.34	6	L	22	V30AE000004		V30AE000007	10	6	0.65	0.16	2	0.29	500
						V30AE000008							
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.65	0.15	2	0.25	500
0.5	6	K	20	V30AE000005	V30AE000007	V30AE000007	12	6	1	0.15	2.6	0.25	500
0.5	6	N	20	V30AE000005	V30AE000008	V30AE000008	14	6	1	0.15	2.6	0.25	500
0.5	10	HL	20	V30AE000007	V30AE000009	V30AE000009	15	10	1	0.15	2.6	0.25	500
0.5	12	L	20	V30AE004188	V30AE004189	V30AE004189	15	12	1	0.15	2.6	0.25	500
0.75	6	K	18	V30AE000008	V30AE000040	V30AE000046	12	6	1.2	0.15	2.8	0.29	500
0.75	6	N	18	V30AE000009	V30AE000041	V30AE000048	14	6	1.2	0.15	2.8	0.29	500
0.75	6	HL	18	V30AE000007	V30AE000050	V30AE000056	15	9	1.2	0.15	2.8	0.29	500
0.75	10	HL	18	V30AE000010	V30AE000042	V30AE000047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000011	V30AE000043	V30AE000048	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000012	V30AE000044	V30AE000049	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000013	V30AE000045	V30AE000046	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000014	V30AE000046	V30AE000048	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000015	V30AE000047	V30AE000047	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500
1.5	6	N	14	V30AE000016	V30AE000048	V30AE000048	14	6	1.7	0.15	3.5	0.28	500
1.5	10	HL	14	V30AE000017	V30AE000049	V30AE000049	15	10	1.7	0.15	3.5	0.28	500

Bezeichnung Description	AWG	Partcode/Serial No. Colour code/Order no.			Normierte mm Dimensions mm						Stück Pieces		
		L ₁	L ₂	Z-#	DRN	KDS	L ₁	L ₂	d ₁	d ₂		S ₁	S ₂
0.14	6	N	26	V30AE000907		V30AE000909	10	6	0.6	0.15	1.5	0.25	500
0.14	6	L	26	V30AE000908		V30AE000910	10	6	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000001		V30AE000002	10	6	0.65	0.16	1.8	0.29	500
						V30AE000044							
0.25	6	L	24	V30AE000002		V30AE000003	10	6	0.65	0.16	1.8	0.29	500
						V30AE000045							
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.65	0.15	1.8	0.25	500
						V30AE000004							
0.34	6	N	22	V30AE000003		V30AE000005	10	6	0.65	0.16	2	0.29	500
						V30AE000006							
0.34	6	L	22	V30AE000004		V30AE000007	10	6	0.65	0.16	2	0.29	500
						V30AE000008							
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.65	0.15	2	0.25	500
0.5	6	K	20	V30AE000005	V30AE000007	V30AE000007	12	6	1	0.15	2.6	0.25	500
0.5	6	N	20	V30AE000005	V30AE000008	V30AE000008	14	6	1	0.15	2.6	0.25	500
0.5	10	HL	20	V30AE000007	V30AE000009	V30AE000009	15	10	1	0.15	2.6	0.25	500
0.5	12	L	20	V30AE004188	V30AE004189	V30AE004189	15	12	1	0.15	2.6	0.25	500
0.75	6	K	18	V30AE000008	V30AE000040	V30AE000046	12	6	1.2	0.15	2.8	0.29	500
0.75	6	N	18	V30AE000009	V30AE000041	V30AE000048	14	6	1.2	0.15	2.8	0.29	500
0.75	6	HL	18	V30AE000007	V30AE000050	V30AE000056	15	9	1.2	0.15	2.8	0.29	500
0.75	10	HL	18	V30AE000010	V30AE000042	V30AE000047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000011	V30AE000043	V30AE000048	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000012	V30AE000044	V30AE000049	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000013	V30AE000045	V30AE000046	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000014	V30AE000046	V30AE000048	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000015	V30AE000047	V30AE000047	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500
1.5	6	N	14	V30AE000016	V30AE000048	V30AE000048	14	6	1.7	0.15	3.5	0.28	500
1.5	10	HL	14	V30AE000017	V30AE000049	V30AE000049	15	10	1.7	0.15	3.5	0.28	500

