

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000039

0.5mm² x 10mm Ferrule - White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	White
Cross section max	0.5 mm ²
Rated wire cross section to (AWG)	20
Standard	UL (DIN)/French Standard

DIMENSIONS

Length	16 mm
Length of tube	10 mm
Stripping length	12 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.6 mm

Diameter of tube	1 mm
------------------	------

MATERIALS



Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.09 g
Pack size	500



Bezeichnung Description	AWG	Partcode/Serial No.	Partcode/Serial No.	DRN	KDS	Minimale mm Dimensions mm				Stück Pieces			
mmF	L ₁	L ₂	Z-#	DRN	KDS	L ₁	L ₂	d ₁	d ₂	VPE			
0.14	6	N	26	V30AE000907		V30AE000909	10	6	0.6	0.15	1.5	0.25	500
0.14	6	L	26	V30AE000908		V30AE000910	10	6	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000901		V30AE000902	10	6	0.6	0.15	1.5	0.25	500
						V30AE000904							
0.25	6	L	24	V30AE000902		V30AE000903	10	6	0.6	0.15	1.5	0.25	500
						V30AE000905							
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.65	0.15	1.5	0.25	500
						V30AE000904							
0.34	6	N	22	V30AE000903		V30AE000905	10	6	0.6	0.15	2	0.25	500
						V30AE000906							
0.34	6	L	22	V30AE000904		V30AE000907	10	6	0.6	0.15	2	0.25	500
						V30AE000908							
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.65	0.15	2	0.25	500
0.5	6	K	20	V30AE000905	V30AE000907	V30AE000907	12	6	1	0.15	2.8	0.25	500
0.5	6	N	20	V30AE000905	V30AE000908	V30AE000908	14	6	1	0.15	2.8	0.25	500
0.5	10	HL	20	V30AE000907	V30AE000909	V30AE000909	15	10	1	0.15	2.8	0.25	500
0.5	12	L	20	V30AE004188	V30AE004189	V30AE004189	15	12	1	0.15	2.8	0.25	500
0.75	6	K	18	V30AE000908	V30AE000940	V30AE000946	12	6	1.2	0.15	2.8	0.25	500
0.75	6	N	18	V30AE000909	V30AE000941	V30AE000948	14	6	1.2	0.15	2.8	0.25	500
0.75	6	HL	18	V30AE000907	V30AE000908	V30AE000908	15	9	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V30AE000910	V30AE000942	V30AE000947	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000911	V30AE000943	V30AE000948	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000912	V30AE000944	V30AE000944	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000913	V30AE000945	V30AE000945	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000914	V30AE000946	V30AE000946	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000915	V30AE000947	V30AE000947	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000916	V30AE000948	V30AE000948	12	6	1.7	0.15	3.5	0.25	500
1.5	6	N	14	V30AE000916	V30AE000948	V30AE000948	14	6	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE000917	V30AE000949	V30AE000949	15	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description	AWG	Partcode/Serial No. Colour code/Order no.			Dimensions Dimensions mm			Stück Pieces					
mmF	L ₁	L ₂	Z-#	DRN	KDS	L ₁	L ₂	d ₁	d ₂	VPE			
0.14	6	N	26	V30AE000907		V30AE000909	10	6	0.6	0.15	1.5	0.25	500
0.14	6	L	26	V30AE000908		V30AE000910	10	6	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000901		V30AE000902	10	6	0.6	0.15	1.5	0.25	500
						V30AE000904							
0.25	6	L	24	V30AE000902		V30AE000903	10	6	0.6	0.15	1.5	0.25	500
						V30AE000905							
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.65	0.15	1.5	0.25	500
						V30AE000904							
0.34	6	N	22	V30AE000903		V30AE000905	10	6	0.6	0.15	2	0.25	500
						V30AE000906							
0.34	6	L	22	V30AE000904		V30AE000907	10	6	0.6	0.15	2	0.25	500
						V30AE000908							
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.65	0.15	2	0.25	500
0.5	6	K	20	V30AE000905	V30AE000907	V30AE000907	12	6	1	0.15	2.8	0.25	500
0.5	6	N	20	V30AE000905	V30AE000908	V30AE000908	14	6	1	0.15	2.8	0.25	500
0.5	10	HL	20	V30AE000907	V30AE000909	V30AE000909	15	10	1	0.15	2.8	0.25	500
0.5	12	L	20	V30AE004188	V30AE004189	V30AE004189	15	12	1	0.15	2.8	0.25	500
0.75	6	K	18	V30AE000908	V30AE000940	V30AE000946	12	6	1.2	0.15	2.8	0.25	500
0.75	6	N	18	V30AE000909	V30AE000941	V30AE000948	14	6	1.2	0.15	2.8	0.25	500
0.75	6	HL	18	V30AE000907	V30AE000908	V30AE000908	15	9	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V30AE000910	V30AE000942	V30AE000947	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000911	V30AE000943	V30AE000948	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000912	V30AE000944	V30AE000944	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000913	V30AE000945	V30AE000945	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000914	V30AE000946	V30AE000946	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000915	V30AE000947	V30AE000947	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000916	V30AE000948	V30AE000948	12	6	1.7	0.15	3.5	0.25	500
1.5	6	N	14	V30AE000916	V30AE000948	V30AE000948	14	6	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE000917	V30AE000949	V30AE000949	15	10	1.7	0.15	3.5	0.25	500

