

## INSULATED BOOTLACE FERRULES

### 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30AE000008

0.75mm<sup>2</sup> x 6mm Ferrule - White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

## TECHNICAL DATA

### GENERAL DATA

Colour	White
Cross section max	0.75 mm <sup>2</sup>
Rated wire cross section to (AWG)	18
Standard	German Standard

### DIMENSIONS

Length	12 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.8 mm

Diameter of tube	1.2 mm
------------------	--------

## MATERIALS



Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

## APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.09 g
Pack size	500



Bezeichnung Description	AWG	Partcode/Serial No. Colour code/Order no.	DRN	KDS	Minimale mm Dimensions mm	Stück Pieces							
mmF	L <sub>1</sub>	L <sub>2</sub>	Z-#	DRN	L <sub>1</sub>	L <sub>2</sub>	d <sub>1</sub>	d <sub>2</sub>	S <sub>1</sub>	S <sub>2</sub>	VPE		
0.14	6	N	26	V30AE000907	V30AE000909	10	6	0.6	0.15	1.5	0.25	500	
0.14	6	L	26	V30AE000908	V30AE000910	10	6	0.6	0.15	1.5	0.25	500	
0.25	6	N	24	V30AE000001	V30AE000002	10	6	0.65	0.16	1.8	0.29	500	
					V30AE000044								
0.25	6	L	24	V30AE000002	V30AE000003	10	6	0.65	0.16	1.8	0.29	500	
					V30AE000045								
0.25	12	LS	24	V30AE004185	V30AE004184	15	12	0.65	0.15	1.8	0.25	500	
					V30AE000004								
0.34	6	N	22	V30AE000003	V30AE000005	10	6	0.65	0.16	2	0.29	500	
					V30AE000006								
0.34	6	L	22	V30AE000004	V30AE000007	10	6	0.65	0.16	2	0.29	500	
					V30AE000008								
0.34	12	LS	22	V30AE004186	V30AE004187	15	12	0.65	0.15	2	0.25	500	
0.5	6	K	20	V30AE000005	V30AE000007	12	6	1	0.15	2.6	0.25	500	
0.5	6	N	20	V30AE000005	V30AE000008	14	6	1	0.15	2.6	0.25	500	
0.5	10	HL	20	V30AE000007	V30AE000009	15	10	1	0.15	2.6	0.25	500	
0.5	12	L	20	V30AE004188	V30AE004189	15	12	1	0.15	2.6	0.25	500	
0.75	6	K	18	V30AE000008	V30AE000040	V30AE000046	12	6	1.2	0.15	2.8	0.29	500
0.75	6	N	18	V30AE000009	V30AE000041	V30AE000048	14	6	1.2	0.15	2.8	0.29	500
0.75	6	HL	18	V30AE000007	V30AE000050	V30AE000056	15	6	1.2	0.15	2.8	0.29	500
0.75	10	HL	18	V30AE000010	V30AE000042	V30AE000047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000011	V30AE000043	V30AE000048	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000012	V30AE000044	V30AE000049	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000013	V30AE000045	V30AE000046	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000014	V30AE000046	V30AE000048	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000015	V30AE000047	V30AE000047	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500
1.5	6	N	14	V30AE000016	V30AE000048	V30AE000048	14	6	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE000017	V30AE000049	V30AE000049	15	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description	AWG	Part Type	Partcode/Serial No. Colour code/Order no.	DRN	KDS	Minimale mm Dimensions mm						Stück Pieces	
mmF	L <sub>1</sub>	L <sub>2</sub>	Z-#	DRN	KDS	L <sub>1</sub>	L <sub>2</sub>	d <sub>1</sub>	d <sub>2</sub>	S <sub>1</sub>	S <sub>2</sub>	VPE	
0.14	6	N	26	V30AE000907		V30AE000909	10	6	0.6	0.15	1.5	0.25	500
0.14	6	L	26	V30AE000908		V30AE000910	10	6	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000001		V30AE000002	10	6	0.65	0.16	1.8	0.29	500
						V30AE000044							
0.25	6	L	24	V30AE000002		V30AE000003	10	6	0.65	0.16	1.8	0.29	500
						V30AE000045							
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.65	0.15	1.8	0.25	500
						V30AE000004							
0.34	6	N	22	V30AE000003		V30AE000005	10	6	0.65	0.16	2	0.29	500
						V30AE000006							
0.34	6	L	22	V30AE000004		V30AE000007	10	6	0.65	0.16	2	0.29	500
						V30AE000008							
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.65	0.15	2	0.25	500
0.5	6	K	20	V30AE000005	V30AE000007	V30AE000007	12	6	1	0.15	2.6	0.25	500
0.5	6	N	20	V30AE000005	V30AE000008	V30AE000008	14	6	1	0.15	2.6	0.25	500
0.5	10	HL	20	V30AE000007	V30AE000009	V30AE000009	15	10	1	0.15	2.6	0.25	500
0.5	12	L	20	V30AE004188	V30AE004189	V30AE004189	15	12	1	0.15	2.6	0.25	500
0.75	6	K	18	V30AE000008	V30AE000040	V30AE000046	12	6	1.2	0.15	2.8	0.29	500
0.75	6	N	18	V30AE000009	V30AE000041	V30AE000048	14	6	1.2	0.15	2.8	0.29	500
0.75	6	HL	18	V30AE000007	V30AE000050	V30AE000056	15	6	1.2	0.15	2.8	0.29	500
0.75	10	HL	18	V30AE000010	V30AE000042	V30AE000047	15	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000011	V30AE000043	V30AE000048	15	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000012	V30AE000044	V30AE000049	12	6	1.4	0.15	3	0.25	500
1	6	N	16	V30AE000013	V30AE000045	V30AE000046	14	6	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000014	V30AE000046	V30AE000048	15	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000015	V30AE000047	V30AE000047	15	12	1.4	0.15	3	0.25	500
1.5	6	K	14	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500
1.5	6	N	14	V30AE000016	V30AE000048	V30AE000048	14	6	1.7	0.15	3.5	0.25	500
1.5	10	HL	14	V30AE000017	V30AE000049	V30AE000049	15	10	1.7	0.15	3.5	0.25	500

