

INSULATED BOOTLACE FERRULES

0.14MM² TO 4MM²

V30AE000041

0.75mm² x 8mm Ferrule - Grey

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Grey
Cross section max	0.75 mm ²
Rated wire cross section to (AWG)	18
Standard	UL (DIN) Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.8 mm

Diameter of tube	1.2 mm
------------------	--------

MATERIALS


Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS


DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.09 g
Pack size	500



Bezeichnung Beschreibung	AVG	Periodenbezeichnung Color code/Order Nr.	Periodenbezeichnung Maßnahmen	Bezugs- Punkte									
mm	kg	Typ											
ZUF	DN	KDS	L ₁	L ₂	L ₃	S ₁	S ₂	S ₃	VPE				
0,04	8	N	26	V3040000067	V3040000069	10	8	0,6	0,15	0,15	0,25	800	
0,04	8	L	26	V3040000068	V3040000069	12	8	0	0,6	0,15	0,15	0,25	800
0,25	8	N	24	V3040000002	V3040000004	10	8	0,6	0,15	0,15	0,25	800	
0,25	8	L	24	V3040000002	V3040000004	12	8	0,6	0,15	0,15	0,25	800	
0,25	8	L	24	V3040000002	V3040000002	12	8	0,6	0,15	0,15	0,25	800	
0,25	12	L3	24	V3040000485	V3040000484	16	12	0,6	0,15	0,15	0,25	800	
0,34	8	N	22	V3040000003	V3040000004	10	8	0,6	0,15	0,15	0,25	800	
0,34	8	L	22	V3040000003	V3040000003	12	8	0,6	0,15	0,15	0,25	800	
0,34	12	L3	22	V3040000486	V3040000487	16	12	0,6	0,15	0,15	0,25	800	
0,34	12	L3	22	V3040000486	V3040000487	16	12	0,6	0,15	0,15	0,25	800	
0,5	8	K	20	V3040000005	V3040000007	12	6	1	0,15	0,25	0,25	800	
0,5	8	N	20	V3040000005	V3040000008	14	8	1	0,15	0,25	0,25	800	
0,5	8	L	20	V3040000005	V3040000009	16	10	1	0,15	0,25	0,25	800	
0,5	12	L	20	V3040000005	V3040000009	16	12	1	0,15	0,25	0,25	800	
0,75	8	K	18	V3040000006	V3040000040	12	6	1	0,15	0,25	0,25	800	
0,75	8	N	18	V3040000009	V3040000041	14	8	1	0,15	0,25	0,25	800	
0,75	8	HLS	18	V3040000097	V3040000088	16	12	1	0,15	0,25	0,25	800	
0,75	10	HL	18	V3040000030	V3040000042	16	10	1	0,15	0,25	0,25	800	
0,75	12	L	18	V3040000001	V3040000045	16	12	1	0,15	0,25	0,25	800	
1	8	K	16	V3040000002	V3040000044	12	6	1	0,15	0,25	0,25	800	
1	8	N	16	V3040000003	V3040000045	14	8	1	0,15	0,25	0,25	800	
1	10	HL	16	V3040000014	V3040000046	16	10	1	0,15	0,25	0,25	800	
1	12	L	16	V3040000076	V3040000047	16	12	1	0,15	0,25	0,25	800	
1,5	8	K	14	V3040000006	V3040000048	12	6	1	0,15	0,15	0,15	800	
1,5	8	N	14	V3040000006	V3040000048	14	8	1	0,15	0,15	0,15	800	
1,5	10	HL	14	V3040000007	V3040000049	16	10	1	0,15	0,15	0,15	800	



Beschreibung Description		AVG	Feldcode/Detail Nr. Field code/Detail no.		Normierte Nr. Normalized no.						Stütz Punkte	
mm	ft	Typ	ZUF	DN	K09	L1	L4	L5	L6	Stütz Punkte		
0.04	1/4	N	26	V304000067	V304000069	10	8	0.8	0.15	0.25	0.00	
0.04	1/4	N	26	V304000068	V304000070	12	8	0.8	0.15	0.15	0.25	0.00
0.25	1	N	24	V304000001	V304000002	10	8	0.8	0.15	0.15	0.25	0.00
0.25	1	N	24	V304000002	V304000004	10	8	0.8	0.15	0.15	0.25	0.00
0.25	1	N	24	V304000003	V304000005	12	8	0.8	0.15	0.15	0.25	0.00
0.25	1/2	L3	24	V304004008	V304004004	16	12	0.8	0.15	0.15	0.25	0.00
0.32	6	N	22	V304000003	V304000004	10	8	0.8	0.15	0.15	0.25	0.00
0.32	6	N	22	V304000004	V304000006	10	8	0.8	0.15	0.15	0.25	0.00
0.34	1	L3	22	V304004006	V304004007	10	8	0.8	0.15	0.15	0.25	0.00
0.34	1/2	L3	22	V30404006	V304004007	10	12	0.8	0.15	0.15	0.25	0.00
0.5	6	K	20	V304000005	V304000007	12	8	1	0.15	0.25	0.05	0.00
0.5	6	N	20	V304000006	V304000008	14	8	1	0.15	0.25	0.05	0.00
0.5	6	N	20	V304000007	V304000009	14	8	1	0.15	0.25	0.05	0.00
0.5	12	L	20	V304000008	V304004009	16	12	1	0.15	0.25	0.05	0.00
0.75	6	N	18	V304000009	V304004010	16	12	1	0.15	0.25	0.05	0.00
0.75	6	N	18	V304000010	V304004011	14	8	1.2	0.15	0.25	0.05	0.00
0.75	9	HLS	18	V304000007	V304000008	15	12	0.15	0.25	0.05	0.05	0.00
0.75	10	HL	18	V304000010	V304004012	16	12	0.15	0.25	0.05	0.05	0.00
0.75	12	L	18	V304000011	V304004013	16	12	0.15	0.25	0.05	0.05	0.00
1	8	K	18	V304000012	V304004014	16	12	1.4	0.15	0.3	0.05	0.00
1	8	N	18	V304000013	V304004015	14	8	1.4	0.15	0.3	0.05	0.00
1	10	HL	18	V304000014	V304004016	16	10	1.4	0.15	0.3	0.05	0.00
1	12	L	18	V304000015	V304004017	16	12	1.4	0.15	0.3	0.05	0.00
1.5	8	K	16	V304000016	V304004018	16	12	1.7	0.15	0.35	0.05	0.00
1.5	8	N	16	V304000017	V304004019	14	8	1.7	0.15	0.35	0.05	0.00
1.5	10	HL	16	V304000018	V304004020	16	12	1.7	0.15	0.35	0.05	0.00

