


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000546 0.75mm² x 6mm Ferrule - Light Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	0.75 mm²
Rated wire cross section to (AWG)	18
Standard	French Standard
DIMENCIONS	

DIMENSIONS

Length	12 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.8 mm

Diameter of tube 1	.2 mm
--------------------	-------

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C


APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.09 g
Pack size	500







	CHICTO MINUTED		AWG		Participal Section No. Colour code/Crabrys.			Nervrinde mm Dkreneure mm					
03/1/2	14.	Typ*		26	DN	H09	14	14	16,	8,	d _a	57	VPE
0.14	: 6	.14	26	V20AE009667		VOCAECONOCE	:10	0.	0.6	0.15	1.5	0.25	500
0.14	0		26	VSOAE001968		V35A5001661	12	8	0.0	0.15	1.5	0.25	500
0.26	8	N	24	VSOABOODOON		V00AE001082	10	6	0.26	0.15	1.8	0.26	500
	272	97	177			V00A0001644	15	0.00	0.00				
0.26			24	VODAEDDOOD		VOCABOOHBELL	-12		0.88	0.15	-1.0		800
		7	2.4	***************************************		V304E001646	100	1.70		U.15	2.4	0.26	
0.15	12	LS	24	VSOAEDD4155		V30AE004154	-16	12	0.65	0.15	1.0	0.25	500
0.34						V90AE001864	10			0.1s	2	0.26	500
0,38	- 6	N	22	V30AE000003		V304E000535	10	ě	0.65				
						V90AE001666				0.16	2	0.25	100
0,54	-8	1.	53	V30AE000004		V30AE008077	12	- 11	0.85				
0.34	- 12	LB	22	V30AE004166		V00AE004187	16	12	0.88	0.15	2	0.26	500
0.5	0	К	20	V30AE000005	V30AE000037	V30AE000037	12	0		0.15	2.6	0.25	500
0.6	n	N	20	V30AE000006	V90A0000008	VOOAEGOOGGE	.14			0.95	2.0	0.06	500
0.8	10	HL.	20	V304E000007	V3046000039	V304E000039	16	10		0.15	2.6	0.26	800
0.0	: 12	1.	20.	VOOAEDOHISS	VS0AE00-HS9	V30AE00HS9	303	12		0.15	2.0	0.25	500
0.75	: 6	ĸ	18.	V36AE000008	V30AE000040	9/30AE000848	17	6	12	0.15	27.81	0.26	500
0.78	- 6	N	10:	V30AE000009	V30AE0000H1	V35AE000546	14		12	0.15	2.8	0.25	500
0.75	:0	14.5	10	VISAE000087	V304000000	VXXALOOGOB	.15	. 91	52	0.16	2.0	0.26	500
0.75	10	HL.	100	VOCABDOODSO	V30A0000042	V3DAE000047	10	10	12	0.15	2,8	0.25	500
0.78	12	L	18	VSOAE0000H	V30AE000043	V3045000648	55	12	12	0.16	2.8	0.25	500
1	-0	K	15	V004E000010	V3045000044	V30AE0000044	10	0	1.4	0.15	5	0.25	500
	8	N	18	VISOAEDOODIS	V304E000048	V004E000048	34	8	1.4	0.15	3	0.25	500
	30	HL.	18.	V30AE000014	V30AE000048	V3046000048	-10	10	1.4	0.15	3	0.25	800
+	12	L	16.	V30AE000076	VSOAE0000EF	V00AE000047	165	12	1.4	0.15	3	0.25	500
13	.0	к	10	VSGAEDOSTOR	V30AE003706	V30A0001705	12	0		0.15	2.5	025	500
1.6	.0	N	10	V30AE000016	V30A0000045	V30A6000048	110	0	1.7	0.16	3.5	0.26	500
1.6	10	HL	16	V30AE000017	V3048000049	Vanagonness	16	10		0.15	3.5	0.26	500