


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000537 0.75mm² x 8mm Ferrule - Light Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	0.75 mm²
Rated wire cross section to (AWG)	18
Standard	French Standard
DIMENSIONS	

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.8 mm

Diameter of tube 1	.2 mm
--------------------	-------

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C


APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.1 g
Pack size	500







Bezeithnung Description			AWG		First code/Greek No. Cultur code/Crab no.				Nervin	ede me evre mi			Please
(3/1/2	14.	Typ*		26	DN	H09	36	14	(6)	5,	d _i	57	VPE
0.14	: 6	.14	26	V304E009667		VOCAECONOR	:10	.0.	0.6	0.15	1.5	0.25	500
0.14	0		26	VSOAE001988		V30A5001681	12	6	0.0	0.16	1.5	0.25	500
0.26	8	B N 24	94	p4 VapAeppoon		V00A8001082	10		0.26	0.15	1.8	0.26	500
	n	77	2.0			V00A0001644	10	100	0.00				
0.26			24	VOCABIOGROSS		VOCABOOHBELL	-12		0.85	0.15	101	0.26	800
		+	24	V30AE3000002		V904E001646	10	62	0.85	U.15			
0.15	12	LS	24	VSOAEDDATSS		V30AE004154	-16	12	0.05	0.15	1.0	0.25	500
						V98AE001884					2	026	500
0,34	- 6	N.	22	V30AE000003		V304E000535	10	ě	0.65	0.15			
						V90AE001666					2	0.25	100
0,54	-8	1.	55	V30AE000004		V30AE008077	12	- 11	0.86	0.16			
0.34	12	LB	22	V30AE004166		V00AE004187	16	12	0.88	0.15	2	0.26	500
0.5	0	K	201	V00AE000005	V30AE000037	V30AE000037	12	0		0.15	2.6	0.25	500
0.6	n	N.	20	V90AE000000	V30A0000008	VSSAESSOSSE	.94			0.99	2.0	0.06	500
0.8	10	HL.	20	V304E000007	V30AE000039	V304E000039	16	10		0.15	2.6	0.26	800
0.0	: 12	t.	20	VOOREDOHISS	VSOAEOOHISB	V30AE00HS9	303	12		0.15	2.0	0.25	500
0.75	: 6	K	18.	V30AE0000008	V30AE000040	9/30AE000848	17	6	12	0.15	27.81	0.26	500
0.78	- 6	N	10:	V30AE0000009	V30AE0000H1	V35AE000546	14		1.2	0.15	2.8	0.25	500
0.75	:0	14.5	10	VSSAEGOROUP	VSOAKOOODISO	VXXALOOGOB	.15	. 91	52	0.16	2.0	0.26	500
0.75	10	HL.	100	VOCAEDODOTO	V30A0000042	V3DAE000047	10	10	12	0.15	2,8	0.25	500
0.78	12	L	18	VSOABOOSOH -	V30AE000043	V3045000648	55	12	12	0.16	2.8	0.25	500
1	-0	K	18	V304E000010	VS045000044	V30AE0000044	10	0	1.4	0.15	5	0.25	500
	8	N	10.	V304E000013	V304E000048	V004E000048	34	8	1.4	0.15	3	0.25	500
	30	HL.	18.	V30AE000014	V30AE000048	V3046000048	-10	10	1.4	0.15	3	0.25	500
+	12	L	16.	V30AE000076	VOOREDOODET	V00AE000047	165	12	1.4	0.15	3	0.25	500
13	.0	К	10	V90AE009704	V30AE003706	V30A0001705	12	0		0.15	2.5	025	500
1.6	.0	N.	10	V30AE000018	V30A0000045	V30A6000048	110	0	1.7	0.16	3.5	0.26	500
1.6	10	HL	16	V304E000017	V304E000049	Vanagonness	16	10		0.15	3.5	0.26	500