

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE004927

2.08mm² x 12mm Ferrule - Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	2.08 mm ²
Rated wire cross section to (AWG)	14
Standard	(DIN)/French Standard

DIMENSIONS

Length	19 mm
Length of tube	12 mm
Stripping length	10 mm
Thickness of collar	0.3 mm
Thickness of tube	0.15 mm
Diameter of collar	3 mm

Diameter of tube	2.05 mm
------------------	---------

MATERIALS


Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS


DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.1 g
Pack size	500



Beschreibung Description	WEG	ZuF	Partikelcode/Symbol code/ID no.	KDS	L ₁	L ₂	L ₃	L ₄	L ₅	L ₆	Stuf. Punkte
			DN								
0.04	E	N	26	V50A020967	V50A020969	10	8	0.6	0.15	0.15	0.25 500
0.04	E	L	26	V50A020988	V50A020989	12	8	0.6	0.15	0.15	0.25 500
0.25	N	N	24	V50A040001	V50A040002	10	8	0.6	0.15	0.15	0.25 500
0.25	N	N	24	V50A040001	V50A040004	10	8	0.6	0.15	0.15	0.25 500
0.25	N	L	24	V50A040002	V50A040003	12	8	0.6	0.15	0.15	0.25 500
0.25	L	LB	24	V50A040045	V50A040046	10	12	0.6	0.15	0.15	0.25 500
0.25	N	N	22	V50A030003	V50A030004	10	8	0.6	0.15	0.15	0.25 500
0.25	E	L	22	V50A030004	V50A030005	12	8	0.6	0.15	0.15	0.25 500
0.25	E	L	22	V50A030004	V50A030007	10	8	0.6	0.15	0.15	0.25 500
0.25	E	K	20	V50A020096	V50A020097	10	12	0.6	0.15	0.15	0.25 500
0.5	N	N	20	V50A030006	V50A030008	14	8	1	0.15	0.25	0.50 500
0.5	N	N	20	V50A030007	V50A030009	14	8	1	0.15	0.25	0.50 500
0.5	L	L	20	V50A040048	V50A040049	10	12	1	0.15	0.25	0.50 500
0.75	E	K	18	V50A020009	V50A020040	12	8	1	0.15	0.25	0.50 500
0.75	N	N	18	V50A020029	V50A020046	14	8	1	0.15	0.25	0.50 500
0.75	N	H/LB	18	V50A020087	V50A020088	10	9	12	0.15	0.25	0.50 500
0.75	N	HL	18	V50A020102	V50A020147	14	10	12	0.15	0.25	0.50 500
0.75	L	L	18	V50A030001	V50A030043	14	12	1.5	0.15	0.25	0.50 500
1	E	K	18	V50A030032	V50A030044	12	8	14	0.15	0.3	0.50 500
1	E	N	18	V50A030033	V50A030045	14	8	14	0.15	0.3	0.50 500
1	E	K	18	V50A030046	V50A030048	10	10	14	0.15	0.3	0.50 500
1	L	L	18	V50A030047	V50A030047	14	14	14	0.15	0.3	0.50 500
1.5	E	K	16	V50A020074	V50A020075	12	17	0.15	0.15	0.25 500	
1.5	N	N	16	V50A020098	V50A020099	14	8	17	0.15	0.15	0.25 500
1.5	L	HL	16	V50A020017	V50A020049	18	17	0.15	0.15	0.25 500	

[illegible]

