


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²



V30AE004107 2.5mm² x 6mm Ferrule - Grey

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Grey
Cross section max	2.5 mm ²
Rated wire cross section to (AWG)	14
Standard	French Standard
DIMENSIONS	
Length	13 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	4.2 mm

Diameter of tube	2.2 mm
MATERIALS	
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C
APPROVALS	
DIN 46228-4:1990	Yes
DIN 46228-4:1990 DIN 46228-1:1992	Yes No
DIN 46228-1:1992	
DIN 46228-1:1992 ADDITIONAL DATA	No

Pack size

d, S,



500



Beenthung au			ANG	ANG Petrosofie/Bettell-Nr. Cickur codu/Drainina			Nervinette mm Dimensiona mm						Process
(19/17 ²	$\cdot 1_{k}$	Typ*		2.6	ON	K05	36	14	$\langle 0 \rangle$	6,	$\langle \sigma_{\mu} \rangle$	δ_i	. VPE
0,14	: 0	N	26	V20AE001067		VOCAECONOSO	:10	. 6.	0.6	0.15	1.5	0.25	500
0.14	0		26	VSOAE001968		V3GAE001081	12	8	0.0	0.15	1.5	0.25	500
0.25	5 n N 24		4 VsoAepopoor		VOGAE001082	10		0.85	0.15	1.8	0.26	900	
		100			V3042001644								
	0.26 H L 24			VICAEDODDOZ		VXXAE001683	-12		0.05	0.15	-14		
		24	V30AL000002		V30AE001646	1.00	1.0	0.00	100	1.01	0.25	000	
0.15	12	LS	24	VIOAE004155		V30AE004154	-16	.12	0.05	0.15	1.0	0.75	500
	0.54 6 N					V20AE001084							
0,34		22	V30AE000003		V20AE000535	10		0.05	0,15	2	0.26	509	
	54 8 L 22				V00A0001666								
0,54		V30AE000004		V30AE008677	12	. 1	0.05	0.10	3	0.25	500		
0.34	- 12	LB	22	V30AED04156		V00AE004157	18	12	0.88	0.15	2	0.25	500
0.5	0	к	20	VIOAE000005	V30AE000037	V3045000037	12	. 0		0.15	2.6	0.25	500
0.6	n	N	20	VODAE000005	V004000008	VDDAEDOODDB	.94			0.95	2.0	0.25	500
0.8	13	HL	20	V354E000007	V3045000039	V304E000039	.45	10		0.15	2.0	0.29	800
0.0	- 12	L.	20	VOOAE004158	VS04500-His9	VIOAEDOHISB	30	12		0.15	2.0	0.25	100
0.75	. 6	ĸ	18.	VOIGAECODODOB	V3042000040	V3042000548	17	-6	12	0.15	2.8	0.25	500
0,75	- 8	Ň	10	VIIAAE000009	V3046000041	V304E000546	14		4.2	0.15	2,0	0.25	500
0,75	:0	14.5	10	VISAE000087	VIOAE000080	VIOADOOOBB	.15	. 9	.62	0.10	-2.0	0,25	500
0.75	- 10	HL	10	VIOAEDODD10	VIOAE000042	V3048000047	50	90	12	0.15	2,8	0.25	500
0.75	12	L	18	VICAE000011	V30AE000043	V3042000548	55	12	12	0.15	2.8	0.25	500
1	.0	ĸ	15	V3046000012	V3045000044	VODAEDOOD4+	10	- e	1.4	0.15	5	0.25	500
	8	Ň	10	V3042000013	V3046000045	V004E000045	34	8	1.4	0.15	3	0.25	500
	30	HL.	18.	V304E000014	V3048000046	V3046000048	-18	90	.14	0.15	3	0.25	800
÷.	-12	1	18.	VS0AE000075	VOOAEDDDD#7	100AE000047	15	12	1.4	0.15	3	0.25	500
13	. a	ĸ	10	VIDAE003704	V30AE001705	V30AD001705	12			0.15	2.5	0.25	500
1.6 :	0	N	10	VIOAE000018	1000A2000045	V0046000048	-14		1.7	0.16	3.6	0.26	600
1.6	10	HL	16	V304E000017	V3048000049	Vaparocookk	14	10		0.15	2.5	0.25	500

S