

INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000062

16mm² x 12mm Ferrule - Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------------------|--------------------|
| Colour | Blue |
| Cross section max | 16 mm ² |
| Rated wire cross section to (AWG) | 6 |
| Standard | UL (DIN) Standard |

DIMENSIONS

| | |
|---------------------|--------|
| Length | 22 mm |
| Length of tube | 12 mm |
| Stripping length | 15 mm |
| Thickness of collar | 0.4 mm |
| Thickness of tube | 0.2 mm |
| Diameter of collar | 8.8 mm |

| | |
|------------------|--------|
| Diameter of tube | 5.8 mm |
|------------------|--------|

MATERIALS

| | |
|----------------------------|----------------------------|
| Conductor tube | Copper alloy |
| Contact surface | Galvanic tin-plated, shiny |
| Plastic collar | Polypropylene-homopolymer |
| Operating temperature from | -5 °C |
| Operating temperature to | 105 °C |

APPROVALS

| | |
|------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 0.74 g |
| Pack size | 100 |