

INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000542

16mm² x 12mm Ferrule - White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Ivory
Cross section max	16 mm ²
Rated wire cross section to (AWG)	6
Standard	French Standard

DIMENSIONS

Length	22 mm
Length of tube	12 mm
Stripping length	15 mm
Thickness of collar	0.4 mm
Thickness of tube	0.2 mm
Diameter of collar	8.8 mm

Diameter of tube	5.8 mm
------------------	--------

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.71 g
Pack size	100