**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000064
25mm² x 16mm Ferrule - Yellow



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6…150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

### PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.
The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.
Euopean manufactured, this range ensures a reliable crimp without splitting.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Colour** | Yellow |
| **Cross section max** | 25 mm² |
| **Rated wire cross section to (AWG)** | 4 |
| **Standard** | UL (DIN) Standard |

## DIMENSIONS

| | |
|---|---|
| **Length** | 30 mm |
| **Length of tube** | 16 mm |
| **Stripping length** | 18 mm |
| **Thickness of collar** | 0.4 mm |
| **Thickness of tube** | 0.2 mm |
| **Diameter of collar** | 11.2 mm |
| **Diameter of tube** | 7.3 mm |

## MATERIALS

| | |
|---|---|
| **Conductor tube** | Copper alloy |
| **Contact surface** | Galvanic tin-plated, shiny |
| **Plastic collar** | Polypropylene-homopolymer |
| **Operating temperature from** | -5 °C |
| **Operating temperature to** | 105 °C |

## APPROVALS

| | |
|---|---|
| **DIN 46228-4:1990** | Yes |
| **DIN 46228-1:1992** | No |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85369010 |
| **Country of origin** | DE |
| **Weight** | 1.47 g |
| **Pack size** | 50 |

