


INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000069

35mm² x 25mm Ferrule - Red

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Cross section max	35 mm ²
Rated wire cross section to (AWG)	2
Standard	UL (DIN) Standard

DIMENSIONS

Length	39 mm
Length of tube	25 mm
Stripping length	28 mm
Thickness of collar	0.4 mm
Thickness of tube	0.2 mm
Diameter of collar	12.7 mm

Diameter of tube	8.3 mm
------------------	--------

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	2.51 g
Pack size	50