


INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000035

50mm² x 20mm Ferrule - Olive

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Olive
Cross section max	50 mm ²
Rated wire cross section to (AWG)	1
Standard	German Standard

DIMENSIONS

Length	36 mm
Length of tube	20 mm
Stripping length	26 mm
Thickness of collar	0.5 mm
Thickness of tube	0.3 mm
Diameter of collar	15 mm

Diameter of tube	10.3 mm
------------------	---------

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	3.25 g
Pack size	50

Bezeichnung Description		AWG	Partcode/Serial No. Cable code/Order no.		Nennweite mm Dimensions mm					Stück Pieces	Bezeichnung Description		AWG	Partcode/Serial No. Cable code/Order no.		Nennweite mm Dimensions mm					Stück Pieces						
mm²	L ₁	Typ Type	Z-#	DRN	KDS	L ₁	L ₂	L ₃	L ₄	VPE	mm²	L ₁	Typ Type	Z-#	DRN	KDS	L ₁	L ₂	L ₃	L ₄	VPE						
0.14	6	N	26	V30AE000957		V30AE000959	10	6	0.6	0.15	1.5	0.25	500	0.14	6	N	26	V30AE000957		V30AE000959	10	6	0.6	0.15	1.5	0.25	500
0.14	8	L	26	V30AE000960		V30AE000961	10	8	0.6	0.15	1.5	0.25	500	0.14	8	L	26	V30AE000960		V30AE000961	10	8	0.6	0.15	1.5	0.25	500
0.25	6	N	24	V30AE000901		V30AE000902	10	6	0.85	0.16	1.8	0.25	500	0.25	6	N	24	V30AE000901		V30AE000902	10	6	0.85	0.16	1.8	0.25	500
						V30AE000944											V30AE000944										
0.25	8	L	24	V30AE000903		V30AE000904	12	8	0.85	0.16	1.8	0.25	500	0.25	8	L	24	V30AE000903		V30AE000904	12	8	0.85	0.16	1.8	0.25	500
						V30AE000945											V30AE000945										
0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.85	0.15	1.8	0.25	500	0.25	12	LS	24	V30AE004185		V30AE004184	15	12	0.85	0.15	1.8	0.25	500
						V30AE000904											V30AE000904										
0.34	6	N	22	V30AE000003		V30AE000005	10	6	0.85	0.16	2	0.25	500	0.34	6	N	22	V30AE000003		V30AE000005	10	6	0.85	0.16	2	0.25	500
						V30AE000006											V30AE000006										
0.34	8	L	22	V30AE000004		V30AE000007	12	8	0.85	0.16	2	0.25	500	0.34	8	L	22	V30AE000004		V30AE000007	12	8	0.85	0.16	2	0.25	500
						V30AE000008											V30AE000008										
0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.85	0.15	2	0.25	500	0.34	12	LS	22	V30AE004186		V30AE004187	15	12	0.85	0.15	2	0.25	500
						V30AE000005											V30AE000005										
0.5	6	K	20	V30AE000005	V30AE000007	V30AE000008	12	6	1	0.15	2.8	0.25	500	0.5	6	K	20	V30AE000005	V30AE000007	V30AE000008	12	6	1	0.15	2.8	0.25	500
0.5	8	N	20	V30AE000006	V30AE000008	V30AE000009	14	8	1	0.15	2.8	0.25	500	0.5	8	N	20	V30AE000006	V30AE000008	V30AE000009	14	8	1	0.15	2.8	0.25	500
0.5	10	HL	20	V30AE000007	V30AE000009	V30AE000010	16	10	1	0.15	2.8	0.25	500	0.5	10	HL	20	V30AE000007	V30AE000009	V30AE000010	16	10	1	0.15	2.8	0.25	500
0.5	12	L	20	V30AE004189		V30AE004188	15	12	1	0.15	2.8	0.25	500	0.5	12	L	20	V30AE004189		V30AE004188	15	12	1	0.15	2.8	0.25	500
0.75	6	K	18	V30AE000008	V30AE000040	V30AE000048	12	6	1.2	0.15	2.8	0.25	500	0.75	6	K	18	V30AE000008	V30AE000040	V30AE000048	12	6	1.2	0.15	2.8	0.25	500
0.75	8	N	18	V30AE000009	V30AE000041	V30AE000049	14	8	1.2	0.15	2.8	0.25	500	0.75	8	N	18	V30AE000009	V30AE000041	V30AE000049	14	8	1.2	0.15	2.8	0.25	500
0.75	9	HL	18	V30AE000087	V30AE000088	V30AE000089	16	9	1.2	0.15	2.8	0.25	500	0.75	9	HL	18	V30AE000087	V30AE000088	V30AE000089	16	9	1.2	0.15	2.8	0.25	500
0.75	10	HL	16	V30AE000009	V30AE000042	V30AE000047	16	10	1.2	0.15	2.8	0.25	500	0.75	10	HL	16	V30AE000009	V30AE000042	V30AE000047	16	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V30AE000009	V30AE000043	V30AE000046	16	12	1.2	0.15	2.8	0.25	500	0.75	12	L	18	V30AE000009	V30AE000043	V30AE000046	16	12	1.2	0.15	2.8	0.25	500
1	6	K	16	V30AE000001	V30AE000044	V30AE000046	12	6	1.4	0.15	3	0.25	500	1	6	K	16	V30AE000001	V30AE000044	V30AE000046	12	6	1.4	0.15	3	0.25	500
1	8	N	16	V30AE000001	V30AE000045	V30AE000048	14	8	1.4	0.15	3	0.25	500	1	8	N	16	V30AE000001	V30AE000045	V30AE000048	14	8	1.4	0.15	3	0.25	500
1	10	HL	16	V30AE000004	V30AE000046	V30AE000048	16	10	1.4	0.15	3	0.25	500	1	10	HL	16	V30AE000004	V30AE000046	V30AE000048	16	10	1.4	0.15	3	0.25	500
1	12	L	16	V30AE000005	V30AE000047	V30AE000047	16	12	1.4	0.15	3	0.25	500	1	12	L	16	V30AE000005	V30AE000047	V30AE000047	16	12	1.4	0.15	3	0.25	500
1.5	6	K	16	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500	1.5	6	K	16	V30AE000704	V30AE000705	V30AE000705	12	6	1.7	0.15	3.5	0.45	500
1.5	8	N	16	V30AE000006	V30AE000048	V30AE000048	14	8	1.7	0.15	3.5	0.25	500	1.5	8	N	16	V30AE000006	V30AE000048	V30AE000048	14	8	1.7	0.15	3.5	0.25	500
1.5	10	HL	16	V30AE000007	V30AE000049	V30AE000049	16	10	1.7	0.15	3.5	0.25	500	1.5	10	HL	16	V30AE000007	V30AE000049	V30AE000049	16	10	1.7	0.15	3.5	0.25	500