

## INSULATED BOOTLACE FERRULES 6MM<sup>2</sup> TO 150MM<sup>2</sup>

V30AE000070

50mm<sup>2</sup> x 20mm Ferrule - Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

## TECHNICAL DATA

### GENERAL DATA

Colour	Blue
Cross section max	50 mm <sup>2</sup>
Rated wire cross section to (AWG)	1
Standard	UL (DIN) Standard

### DIMENSIONS

Length	36 mm
Length of tube	20 mm
Stripping length	26 mm
Thickness of collar	0.5 mm
Thickness of tube	0.3 mm
Diameter of collar	15 mm

Diameter of tube	10.3 mm
------------------	---------

### MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	3.28 g
Pack size	50