OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE002896
120mm² x 30mm Ferrule - Blue



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6…150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.
The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.
Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	120 mm²
Rated wire cross section to (AWG)	4/0
Standard	German Standard

DIMENSIONS

Length	50 mm
Length of tube	30 mm
Stripping length	36 mm
Thickness of collar	0.7 mm
Thickness of tube	0.5 mm
Diameter of collar	21 mm
Diameter of tube	16.5 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	9.21 g
Pack size	25

