


INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE003882

0.14mm² x 6mm Ferrule - Grey, Small Bag

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Grey
Cross section max	0.14 mm ²
Rated wire cross section to (AWG)	26
Standard	German Standard

DIMENSIONS

Length	10 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	1.8 mm
Diameter of tube	0.85 mm

MATERIALS



Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.06 g
Pack size	500



Bezeichnung Description		AWG	Z/F Type	DN	Festbolzen/Schraube Solid screw/Bolt		Nennmaße/mm Dimensions/mm				Stück Pieces		
mm²	l ₁				L ₁	l ₂	r ₁	S ₁	r ₂	S ₂			
0.14	8	N	26	V304E020967		V304E020969	10	8	0.6	0.15	1.5	0.25	500
0.14	8	L	26	V304E020968		V304E020969	12	8	0.6	0.15	1.5	0.25	500
0.25	8	N	24	V304E020001		V304E020982	10	8	0.85	0.15	1.8	0.25	500
0.25	8	L	24	V304E020002		V304E020983	12	8	0.85	0.15	1.8	0.25	500
0.25	12	LS	24	V304E024185		V304E024184	16	12	0.85	0.15	1.8	0.25	500
0.34	8	N	22	V304E020003		V304E020984	10	8	0.85	0.15	2	0.25	500
0.34	8	L	22	V304E020004		V304E020985	12	8	0.85	0.15	2	0.25	500
0.34	12	LS	22	V304E024186		V304E024187	16	12	0.85	0.15	2	0.25	500
0.5	8	K	20	V304E020005	V304E020037	V304E020037	12	8	1	0.15	2.8	0.25	500
0.5	8	N	20	V304E020006	V304E020038	V304E020038	14	8	1	0.15	2.8	0.25	500
0.5	10	HL	20	V304E020007	V304E020039	V304E020039	16	10	1	0.15	2.8	0.25	500
0.5	12	L	20	V304E024188	V304E024189	V304E024189	16	12	1	0.15	2.8	0.25	500
0.75	8	K	18	V304E020008	V304E020040	V304E020046	12	8	1.2	0.15	2.8	0.25	500
0.75	8	N	18	V304E020009	V304E020041	V304E020046	14	8	1.2	0.15	2.8	0.25	500
0.75	9	HLS	18	V304E020007	V304E020080	V304E020088	15	9	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V304E020010	V304E020042	V304E020047	16	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V304E020011	V304E020043	V304E020048	16	12	1.2	0.15	2.8	0.25	500
1	8	K	16	V304E020012	V304E020044	V304E020044	12	8	1.4	0.15	3	0.25	500
1	8	N	16	V304E020013	V304E020045	V304E020045	14	8	1.4	0.15	3	0.25	500
1	10	HL	16	V304E020014	V304E020046	V304E020046	16	10	1.4	0.15	3	0.25	500
1	12	L	16	V304E020015	V304E020047	V304E020047	16	12	1.4	0.15	3	0.25	500
1.5	8	K	16	V304E020016	V304E020048	V304E020048	12	8	1.7	0.15	3.5	0.25	500
1.5	8	N	16	V304E020017	V304E020049	V304E020049	14	8	1.7	0.15	3.5	0.25	500
1.5	10	HL	16	V304E020017	V304E020049	V304E020049	16	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description		AWG	Z-F	DN	KDS	Nennmaße/mm Dimensions/mm						Stück Pieces	
mm²	l ₁ l ₂ Type					L ₁	l ₂	r ₁	S ₁	r ₂	S ₂		
0.14	8	N	26	V304E020967		V304E020969	10	8	0.6	0.15	1.5	0.25	500
0.14	8	L	26	V304E020968		V304E020969	12	8	0.6	0.15	1.5	0.25	500
0.25	8	N	24	V304E020001		V304E020982	10	8	0.85	0.15	1.8	0.25	500
0.25	8	L	24	V304E020002		V304E020983	12	8	0.85	0.15	1.8	0.25	500
0.25	12	LS	24	V304E024185		V304E024184	16	12	0.85	0.15	1.8	0.25	500
0.34	8	N	22	V304E020003		V304E020984	10	8	0.85	0.15	2	0.25	500
0.34	8	L	22	V304E020004		V304E020985	12	8	0.85	0.15	2	0.25	500
0.34	12	LS	22	V304E024186		V304E024187	16	12	0.85	0.15	2	0.25	500
0.5	8	K	20	V304E020005	V304E020037	V304E020037	12	8	1	0.15	2.8	0.25	500
0.5	8	N	20	V304E020006	V304E020038	V304E020038	14	8	1	0.15	2.8	0.25	500
0.5	10	HL	20	V304E020007	V304E020039	V304E020039	16	10	1	0.15	2.8	0.25	500
0.5	12	L	20	V304E024188	V304E024189	V304E024189	16	12	1	0.15	2.8	0.25	500
0.75	8	K	18	V304E020008	V304E020040	V304E020046	12	8	1.2	0.15	2.8	0.25	500
0.75	8	N	18	V304E020009	V304E020041	V304E020046	14	8	1.2	0.15	2.8	0.25	500
0.75	9	HLS	18	V304E020007	V304E020080	V304E020088	15	9	1.2	0.15	2.8	0.25	500
0.75	10	HL	18	V304E020010	V304E020042	V304E020047	16	10	1.2	0.15	2.8	0.25	500
0.75	12	L	18	V304E020011	V304E020043	V304E020048	16	12	1.2	0.15	2.8	0.25	500
1	8	K	16	V304E020012	V304E020044	V304E020044	12	8	1.4	0.15	3	0.25	500
1	8	N	16	V304E020013	V304E020045	V304E020045	14	8	1.4	0.15	3	0.25	500
1	10	HL	16	V304E020014	V304E020046	V304E020046	16	10	1.4	0.15	3	0.25	500
1	12	L	16	V304E020015	V304E020047	V304E020047	16	12	1.4	0.15	3	0.25	500
1.5	8	K	16	V304E020016	V304E020048	V304E020048	12	8	1.7	0.15	3.5	0.25	500
1.5	8	N	16	V304E020017	V304E020049	V304E020049	14	8	1.7	0.15	3.5	0.25	500
1.5	10	HL	16	V304E020017	V304E020049	V304E020049	16	10	1.7	0.15	3.5	0.25	500