


0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE003890 0.5mm² x 8mm Ferrule - Orange, Small Bag

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

Euopean manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Orange
Cross section max	0.5 mm²
Rated wire cross section to (AWG)	20
Standard	German Standard
DIMENGIONO	

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.6 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C


APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.81 g
Pack size	100







	CHICFE MINUTER					Newymotie mm Dengrappis mm						Store Proces	
(13/1/2	14.	Typ*		26	DN	H09	16	14	(6)	6,	d _a	N,	VPE
0.14	: 6	.14	26	V20AE009667		VSGAEGG9669	:10	0.	0.6	0.15	1.5	0.25	500
0.14	0		26	VSOAE001988		V3GAE001681	12	6	0.0	0.16	1.5	0.25	500
0.26	n	N	24	VSOABOODOOT		V00AE001082 V00AE001644	10	6	0.86	0.16	1.8	0.26	500
0.26		1.	24	VOCABIOGROSS		VOIGAEGO16813	-12		0.85		3.8	0.26	800
0.26		*	24	VOOAE000002		V304E001646	12	1.5		0.18			
0.15	12	LS	24	VSOAEDDATSS		V30AE004154	-16	12	0.65	0.15	1.0	0.25	500
			_			V90AE001884				0,ts	2	0.26	500
0,38	- 6	N.	22	V30AE000003		V30AE000535	10	ě	0.65				
						V00AE001666				0.16	2	0.25	100
0,54	-8	1.	55	V30AE000004		V30AE008077	12	2 6	0.80				
0.34	12	LB	22	V30AE004166		V00AE004187	18	12	0.88	0.15	2	0.26	500
0,5	0	K	201	V00AE000005	V30AE000037	V30AE000037	12	0		0.15	2.6	0.25	500
0.6	n	N	20	V30AE000008	VS0A0000008	V00AE000008	.14			0.99	2.0	0.05	500
0.8	10	HL.	20	V304E000007	V30AE000039	V3040000009	16	10		0.15	2.6	0.26	800
0.0	: 12	t.	20	VOOREDOHISS	VSOAEOOHISB	V30AE00H59	303	12		0.15	2.0	0.25	500
0.75	: 6	K	18.	V30AE000008	V30AE000040	V30AE000848	17	6	12	0.15	27.81	0.26	500
0.75	8	N	10	V30AE0000009	V36AE0000H1	V304E000546	14		12	0.15	2.8	0.25	500
0.75	:0	14.5	10	VSSAEGOROUP	VSOAKOOODISO	VIOAGOGGGB	.15	. 91	52	0.16	2.0	0.26	500
0.75	10	HL.	100	VOCAEDODOTO	V30A0000042	V00A0000047	10	10	12	0.15	2,8	0.25	500
0.75	12	L	18	VSOABOOSOH -	V30AE000043	V30AE000648	55	12	12	0.16	2.8	0.25	500
1.	-0	K	18	V304E000010	VS045000044	V70AE0000044	10	0	1.4	0.15	5	0.25	500
	8	N	10.	V304E000013	V304E000048	V304E000048	34	8	1.4	0.15	3	0.25	500
	30	HL.	18.	V30AE000014	V30AE000048	V304E000048	-10	10	1.4	0.15	3	0.25	500
+	12	L	16.	V30AE000076	VOOREDOODET	V00AE000047	165	12	1.4	0.15	3	0.25	500
13	.0	К	10	V90AE009704	V30AE003706	V30A0001705	12	0		0.15	2.5	025	500
1.6	.0	N.	10	V30AE000018	V30A0000045	V00A6000048	110	0	1.7	0.16	3.5	0.26	500
1.5	10	HL.	16	V304E000017	V304E000049	V3046000049	16	10	1.7	0.15	3.5	0.26	500