

## INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE003120

6mm<sup>2</sup> x 12mm Dual Ferrule - Green

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...16 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Colour	Green
Cross section max	6 mm <sup>2</sup>
Rated wire cross section to (AWG)	10
Standard	French Standard

#### DIMENSIONS

Length	23 mm
Length of tube	12 mm
Stripping length	20 mm
Thickness of collar	0.5 mm
Thickness of tube	0.2 mm
Diameter of tube	4.5 mm

#### MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.64 g
Pack size	100

