


TRI-RATED INSULATED FERRULES 0.5MM² TO 1.5MM² 16-20 AWG

V30AE003544

0.5mm² x 8mm 20 AWG Ferrule - Orange

- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------------------|---------------------|
| Colour | Orange |
| Cross section max | 0.5 mm ² |
| Rated wire cross section to (AWG) | 20 |
| Standard | German Standard |

DIMENSIONS

| | |
|---------------------|---------|
| Length | 14 mm |
| Length of tube | 8 mm |
| Stripping length | 10 mm |
| Thickness of collar | 0.25 mm |
| Thickness of tube | 0.15 mm |
| Diameter of collar | 2.9 mm |
| Diameter of tube | 1.1 mm |

MATERIALS

| | |
|----------------|--------------|
| Conductor tube | Copper alloy |
|----------------|--------------|

| | |
|----------------------------|----------------------------|
| Contact surface | Galvanic tin-plated, shiny |
| Plastic collar | Polypropylene-homopolymer |
| Operating temperature from | -5 °C |
| Operating temperature to | 105 °C |

APPROVALS

| | |
|------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | EEC |
| Weight | 0.09 g |
| Pack size | 500 |