OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

TRI-RATED INSULATED FERRULES 0.5MM² TO 1.5MM² 16-20 AWG

V30AE003544
0.5mm² x 8mm 20 AWG Ferrule - Orange



- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Orange
Cross section max	0.5 mm²
Rated wire cross section to (AWG)	20
Standard	German Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.9 mm
Diameter of tube	1.1 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0.09 g
Pack size	500