


## TRI-RATED INSULATED FERRULES 0.5MM<sup>2</sup> TO 1.5MM<sup>2</sup> 16-20 AWG

V30AE003549

1mm<sup>2</sup> x 8mm 18 AWG Ferrule - Red

- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Colour	Red
Cross section max	1 mm <sup>2</sup>
Rated wire cross section to (AWG)	17
Standard	UL (DIN)/French Standard

#### DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	3.5 mm
Diameter of tube	1.4 mm

#### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

**APPROVALS**

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

**ADDITIONAL DATA**

Tariff code	85369010
Country of origin	EEC
Weight	0.12 g
Pack size	500