


## TRI-RATED INSULATED FERRULES 0.5MM<sup>2</sup> TO 1.5MM<sup>2</sup> 16-20 AWG

V30AE000654

1.5mm<sup>2</sup> x 8mm 16 AWG Ferrule - Red

- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.



### PRODUCT DESCRIPTION

## TECHNICAL DATA

### GENERAL DATA

Colour	Red
Cross section max	1.5 mm <sup>2</sup>
Rated wire cross section to (AWG)	16
Standard	German Standard

### DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	4 mm
Diameter of tube	1.7 mm

### MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Operating temperature from</b>	-5 °C
<b>Operating temperature to</b>	105 °C

## APPROVALS

<b>DIN 46228-4:1990</b>	Yes
<b>DIN 46228-1:1992</b>	No

## ADDITIONAL DATA

<b>Tariff code</b>	85369010
<b>Country of origin</b>	EEC
<b>Weight</b>	0.14 g
<b>Pack size</b>	500