OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

TRI-RATED INSULATED FERRULES 0.5MM² TO 1.5MM² 16-20 AWG

V30AE000654
1.5mm² x 8mm 16 AWG Ferrule - Red



- Compatible with various international conductor standards.
- Made of durable tin-plated copper for reliability.
- Available in multiple sizes for diverse applications.
- Designed for easy installation in tight spaces.

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Red
Cross section max	1.5 mm²
Rated wire cross section to (AWG)	16
Standard	German Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	4 mm
Diameter of tube	1.7 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0.14 g
Pack size	500