OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES ON REEL 0.34MM² TO 2.5MM²

V30MA000033
0.5mm² x 8mm Ferrule on Reel - White



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- Material: E-Cu/A-Cu, galvanically tin-plated
- Up to 5000 ferrules in a reel

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	White
Cross section max	0.5 mm²
Rated wire cross section to (AWG)	20
Standard	UL(DIN)/French Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.6 mm
Diameter of tube	1 mm

MATERIALS

Conductor tube	Copper alloy

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.12 g
Pack size	1