

INSULATED BOOTLACE FERRULES ON REEL 0.34MM² TO 2.5MM²

V30MA004825

2.5mm² x 10mm Ferrule on Reel - Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- Material: E-Cu/A-Cu, galvanically tin-plated
- Up to 5000 ferrules in a reel



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	2.5 mm ²
Rated wire cross section to (AWG)	14
Standard	German/UL (DIN) Standard

DIMENSIONS

Length	17 mm
Length of tube	10 mm
Stripping length	12 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	4.2 mm
Diameter of tube	2.2 mm

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.21 g
Pack size	500