OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULES ON REEL 0.34MM² TO 2.5MM²

V30MA004934
0.5mm² x 8mm 20 AWG Reel - White



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- Material: E-Cu/A-Cu, galvanically tin-plated
- Up to 5000 ferrules in a reel

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	White
Cross section max	0.5 mm²
Rated wire cross section to (AWG)	20
Standard	UL (DIN)/French Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.9 mm
Diameter of tube	1.1 mm

MATERIALS

Conductor tube	Copper alloy

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0.09 g
Pack size	4000