


INSULATED BOOTLACE FERRULES
0.14MM² TO 4MM²

V30AE000079

Ferrules 0.5sq-8mm White (pack 100)

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION**

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA**GENERAL DATA**

Colour	White
Cross section max	0.5 mm ²
Rated wire cross section to (AWG)	20
Standard	UL (DIN)/French Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0.25 mm
Thickness of tube	0.15 mm
Diameter of collar	2.6 mm

Diameter of tube 1 mm

MATERIALS

Conductor tube Copper alloy

Contact surface Galvanic tin-plated, shiny

Plastic collar Polypropylene-homopolymer

Operating temperature from -5 °C

Operating temperature to 105 °C

APPROVALS

DIN 46228-4:1990 Yes

DIN 46228-1:1992 No



ADDITIONAL DATA

Tariff code 85369010

Country of origin DE

Weight 0.09 g

Pack size 100



Bezeichnung Description		AWG	Pitchcode/Symbol-Nr. Cable code/Order no.		Nennmaße mm Dimensions mm					Stück Pieces	
mm ²	Typ Type	Z.#	DN	KDS	L ₁	L ₂	ℓ ₁	ℓ ₂	ℓ ₃	VPE	
0.14	B N 26	V30AE029507		V30AE029509	10	8	0.6	0.15	1.5	0.25	500
0.14	B L 26	V30AE029508		V30AE029510	10	8	0.6	0.15	1.5	0.25	500
0.25	B N 24	V30AE030001		V30AE030002	10	8	0.85	0.15	1.8	0.25	500
				V30AE030044							
				V30AE030083							
0.25	B L 24	V30AE030002		V30AE030045	10	8	0.85	0.15	1.8	0.25	500
0.25	B L 24	V30AE030003		V30AE030046	10	8	0.85	0.15	1.8	0.25	500
0.34	B N 22	V30AE030003		V30AE030004	10	8	0.85	0.15	2	0.25	500
				V30AE030085							
				V30AE030086							
0.34	B L 22	V30AE030004		V30AE030087	10	8	0.85	0.15	2	0.25	500
0.34	B L 22	V30AE030005		V30AE030088	10	8	0.85	0.15	2	0.25	500
0.5	B K 20	V30AE030005	V30AE030007	V30AE030007	12	8	1	0.15	2.6	0.25	500
0.5	B N 20	V30AE030005	V30AE030008	V30AE030008	14	8	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030009	V30AE030009	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030010	V30AE030010	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030011	V30AE030011	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030012	V30AE030012	16	10	1	0.15	2.6	0.25	500
0.8	B K 18	V30AE030008	V30AE030040	V30AE030040	12	8	1.2	0.15	2.8	0.25	500
0.75	B L 18	V30AE030009	V30AE030041	V30AE030041	14	8	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030089	V30AE030089	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030090	V30AE030090	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030091	V30AE030091	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030092	V30AE030092	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030093	V30AE030093	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030094	V30AE030094	16	10	1.2	0.15	2.8	0.25	500
1	B K 16	V30AE030012	V30AE030044	V30AE030044	12	8	1.4	0.15	3	0.25	500
1	B N 16	V30AE030013	V30AE030045	V30AE030045	14	8	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030046	V30AE030046	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030047	V30AE030047	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030048	V30AE030048	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030049	V30AE030049	16	10	1.4	0.15	3	0.25	500
1.5	B K 16	V30AE030704	V30AE030705	V30AE030705	12	8	1.7	0.15	3.5	0.25	500
1.5	B N 16	V30AE030016	V30AE030048	V30AE030048	14	8	1.7	0.15	3.5	0.25	500
1.5	HL 16	V30AE030017	V30AE030049	V30AE030049	16	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description		AWG	Pitchcode/Symbol-Nr. Cable code/Order no.		Nennmaße mm Dimensions mm					Stück Pieces	
mm ²	Typ Type	Z.#	DN	KDS	L ₁	L ₂	ℓ ₁	ℓ ₂	ℓ ₃	VPE	
0.14	B N 26	V30AE029507		V30AE029509	10	8	0.6	0.15	1.5	0.25	500
0.14	B L 26	V30AE029508		V30AE029510	10	8	0.6	0.15	1.5	0.25	500
0.25	B N 24	V30AE030001		V30AE030002	10	8	0.85	0.15	1.8	0.25	500
				V30AE030044							
				V30AE030083							
0.25	B L 24	V30AE030002		V30AE030045	10	8	0.85	0.15	1.8	0.25	500
0.25	B L 24	V30AE030003		V30AE030046	10	8	0.85	0.15	1.8	0.25	500
0.34	B N 22	V30AE030003		V30AE030004	10	8	0.85	0.15	2	0.25	500
				V30AE030085							
				V30AE030086							
0.34	B L 22	V30AE030004		V30AE030087	10	8	0.85	0.15	2	0.25	500
0.5	B K 20	V30AE030005	V30AE030007	V30AE030007	12	8	1	0.15	2.6	0.25	500
0.5	B N 20	V30AE030005	V30AE030008	V30AE030008	14	8	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030009	V30AE030009	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030010	V30AE030010	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030011	V30AE030011	16	10	1	0.15	2.6	0.25	500
0.8	HL 20	V30AE030007	V30AE030012	V30AE030012	16	10	1	0.15	2.6	0.25	500
0.75	B K 18	V30AE030008	V30AE030040	V30AE030040	12	8	1.2	0.15	2.8	0.25	500
0.75	B L 18	V30AE030009	V30AE030041	V30AE030041	14	8	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030089	V30AE030089	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030090	V30AE030090	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030091	V30AE030091	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030092	V30AE030092	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030093	V30AE030093	16	10	1.2	0.15	2.8	0.25	500
0.75	B HL 18	V30AE030007	V30AE030094	V30AE030094	16	10	1.2	0.15	2.8	0.25	500
1	B K 16	V30AE030012	V30AE030044	V30AE030044	12	8	1.4	0.15	3	0.25	500
1	B N 16	V30AE030013	V30AE030045	V30AE030045	14	8	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030046	V30AE030046	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030047	V30AE030047	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030048	V30AE030048	16	10	1.4	0.15	3	0.25	500
1	HL 16	V30AE030014	V30AE030049	V30AE030049	16	10	1.4	0.15	3	0.25	500
1.5	B K 16	V30AE030704	V30AE030705	V30AE030705	12	8	1.7	0.15	3.5	0.25	500
1.5	B N 16	V30AE030016	V30AE030048	V30AE030048	14	8	1.7	0.15	3.5	0.25	500
1.5	HL 16	V30AE030017	V30AE030049	V30AE030049	16	10	1.7	0.15	3.5	0.25	500

