OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE000619
Ferrules 0.75sq-8mm Blue (pack 100)



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5…16 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Colour** | Blue |
| **Cross section max** | 0.75 mm² |
| **Rated wire cross section to (AWG)** | 18 |
| **Standard** | French Standard |

## DIMENSIONS

| | |
|---|---|
| **Length** | 14 mm |
| **Length of tube** | 8 mm |
| **Stripping length** | 10 mm |
| **Thickness of collar** | 0.25 mm |
| **Thickness of tube** | 0.15 mm |
| **Diameter of collar** | 2.8 mm |
| **Diameter of tube** | 1.2 mm |

## MATERIALS

| | |
|---|---|
| **Conductor tube** | Copper alloy |
| **Contact surface** | Galvanic tin-plated, shiny |

| | |
|---|---|
| **Plastic collar** | Polypropylene-homopolymer |
| **Operating temperature from** | -5 °C |
| **Operating temperature to** | 105 °C |

## APPROVALS

| | |
|---|---|
| **DIN 46228-4:1990** | Yes |
| **DIN 46228-1:1992** | No |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85369010 |
| **Country of origin** | DE |
| **Weight** | 0.1 g |
| **Pack size** | 500 |









