


INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE000621

4mm² x 10mm Ferrule - Orange - Erou Pack

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...16 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Orange
Cross section max	4 mm ²
Rated wire cross section to (AWG)	12
Standard	French Standard

DIMENSIONS

Length	18 mm
Length of tube	10 mm
Stripping length	12 mm
Thickness of collar	0.3 mm
Thickness of tube	0.2 mm
Diameter of collar	4.8 mm
Diameter of tube	2.8 mm

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.26 g
Pack size	500

