OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE000621
4mm² x 10mm Ferrule - Orange - Erou Pack



- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5…16 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Orange
Cross section max	4 mm²
Rated wire cross section to (AWG)	12
Standard	French Standard

DIMENSIONS

Length	18 mm
Length of tube	10 mm
Stripping length	12 mm
Thickness of collar	0.3 mm
Thickness of tube	0.2 mm
Diameter of collar	4.8 mm
Diameter of tube	2.8 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.26 g
Pack size	500







