



SIGNAL TOWER Ø 40MM ECO

902012405

LED Steady, Red, 24 V ac/dc, ZDC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes

- LED steady light

- LED flashing light

- LED strobe light (single flash)

- LED multi strobe light (multi flash)

- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

TECHNICAL DATA

DATA

| | |
|-------------|------|
| Lens colour | Red |
| IP class | IP66 |

| | |
|-----------------------------|---------|
| Light source | LED |
| Light type | Red LED |
| Supply voltage | 24 V |
| Mounting | Bayonet |
| Nominal current max | 0.033 A |
| Temperature operational min | -30 °C |
| Temperature operational max | 60 °C |
| Weight | 43 g |
| | |
| Number of optional modules | 2 |
| Supply voltage ac/dc max | 26.4 V |
| Supply voltage ac/dc min | 21.6 V |
| Diameter | 40 mm |
| Nominal current min | 0.022 A |

