



## SIGNAL TOWER Ø 40MM ECO

902032313

LED Strobe, Red, 230-240 V ac, ZDF

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes

- LED steady light

- LED flashing light

- LED strobe light (single flash)

- LED multi strobe light (multi flash)

- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

## TECHNICAL DATA

### DATA

Lens colour	Red
IP class	IP66

<b>Light source</b>	LED
<b>Light type</b>	Red LED
<b>Supply voltage</b>	230 V
<b>Supply voltage ac max</b>	253 V AC
<b>Supply voltage ac min</b>	207 V AC
<b>Mounting</b>	Bayonet
<b>Nominal current max</b>	0.01 A
<b>Temperature operational min</b>	-30 °C
<b>Temperature operational max</b>	60 °C
<b>Weight</b>	43 g
<b>Number of optional modules</b>	2
<b>Diameter</b>	40 mm
<b>Flash frequency</b>	1.4 Hz
<b>Nominal current min</b>	0.01 A

