**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# SIGNAL TOWER Ø 40MM ECO

902044313
LED Multi-strobe, Clear, 230-240 V ac, ZFF

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes

- LED steady light

- LED flashing light

- LED strobe light (single flash)

- LED multi strobe light (multi flash)

- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

# TECHNICAL DATA

## DATA

| | |
|---|---|
| **Lens colour** | Clear |
| **IP class** | IP66 |

| | |
|---|---|
| **Light source** | LED |
| **Light type** | White LED |
| **Supply voltage** | 230 V |
| **Supply voltage ac max** | 253 V AC |
| **Supply voltage ac min** | 207 V AC |
| **Mounting** | Bayonet |
| **Nominal current max** | 0.03 A |
| **Temperature operational min** | -30 °C |
| **Temperature operational max** | 60 °C |
| **Weight** | 43 g |

| | |
|---|---|
| **Number of optional modules** | 2 |
| **Diameter** | 40 mm |
| **Flash frequency** | 2.6 Hz |
| **Nominal current min** | 0.021 A |

