



## SIGNAL TOWER Ø 60MM ECO

901051405

LED Steady, Amber, 24 V ac/dc, YDC-HP

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

- The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,
- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

## TECHNICAL DATA

### DATA

|                     |            |
|---------------------|------------|
| Lens colour         | Orange     |
| IP class            | IP66       |
| Light source        | LED        |
| Light type          | Orange LED |
| Supply voltage      | 24 V       |
| Mounting            | Bayonet    |
| Nominal current max | 0.15 A     |

|                             |        |
|-----------------------------|--------|
| Temperature operational min | -30 °C |
| Temperature operational max | 60 °C  |
| Weight                      | 73 g   |

|                            |        |
|----------------------------|--------|
| Number of optional modules | 2      |
| Supply voltage ac/dc max   | 26 V   |
| Supply voltage ac/dc min   | 18 V   |
| Diameter                   | 60 mm  |
| Nominal current min        | 0.13 A |

