



SIGNAL TOWER Ø 70MM ECO

900007900

Steady, Yellow, 12-250 V ac/dc, XLL

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

TECHNICAL DATA

DATA

Lens colour	Yellow
IP class	IP66
Light source	Bulb
Light type	Bulb
Supply voltage	250 V
Mounting	Bayonet

Temperature operational min	-30 °C
-----------------------------	--------

Temperature operational max	60 °C
-----------------------------	-------

Weight	72 g
--------	------

Number of optional modules	2
----------------------------	---

Diameter	70 mm
----------	-------

Lamp power	7 W
------------	-----

Lamp socket	Ba15d
-------------	-------









