



## SIGNAL TOWER Ø 70MM ECO

900016313

LED Steady, Green, 230-240 V ac, XDC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### TECHNICAL DATA

#### DATA

|                       |           |
|-----------------------|-----------|
| Lens colour           | Green     |
| IP class              | IP66      |
| Light source          | LED       |
| Light type            | Green LED |
| Supply voltage        | 230 V     |
| Supply voltage ac max | 253 V AC  |

|                             |          |
|-----------------------------|----------|
| Supply voltage ac min       | 207 V AC |
| Mounting                    | Bayonet  |
| Nominal current max         | 0.028 A  |
| Temperature operational min | -30 °C   |
| Temperature operational max | 60 °C    |
| Weight                      | 100 g    |
|                             |          |
| Number of optional modules  | 2        |
| Diameter                    | 70 mm    |
| Nominal current min         | 0.027 A  |









