



## SIGNAL TOWER Ø 70MM ECO

900035405

LED Strobe, Blue, 24 V ac/dc, XDF

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

## TECHNICAL DATA

### DATA

|                |          |
|----------------|----------|
| Lens colour    | Blue     |
| IP class       | IP66     |
| Light source   | LED      |
| Light type     | Blue LED |
| Supply voltage | 24 V     |
| Mounting       | Bayonet  |

|                             |         |
|-----------------------------|---------|
| Nominal current max         | 0.135 A |
| Temperature operational min | -30 °C  |
| Temperature operational max | 60 °C   |
| Weight                      | 100 g   |
| Number of optional modules  | 2       |
| Supply voltage ac/dc max    | 26.4 V  |
| Supply voltage ac/dc min    | 21.6 V  |
| Diameter                    | 70 mm   |
| Flash frequency             | 1.4 Hz  |
| Nominal current min         | 0.13 A  |









