



SIGNAL TOWER Ø 70MM ECO

900037313

LED Strobe, Yellow, 230-240 V ac, XDF

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

TECHNICAL DATA

DATA

Lens colour	Yellow
IP class	IP66
Light source	LED
Light type	Yellow LED
Supply voltage	230 V
Supply voltage ac max	253 V AC

Supply voltage ac min	207 V AC
Mounting	Bayonet
Nominal current max	0.01 A
Temperature operational min	-30 °C
Temperature operational max	60 °C
Weight	100 g
Number of optional modules	2
Diameter	70 mm
Flash frequency	1.4 Hz
Nominal current min	0.01 A









