**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# SIGNAL TOWER Ø 70MM ECO

900052405
LED Steady, Red, 24 V ac/dc, XDC-HP

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range

### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

# TECHNICAL DATA

## DATA

| | |
|---|---|
| **Lens colour** | Red |
| **IP class** | IP66 |
| **Light source** | LED |
| **Light type** | Red LED |
| **Supply voltage** | 24 V |
| **Mounting** | Bayonet |

| | |
|---|---|
| **Nominal current max** | 0.2 A |
| **Temperature operational min** | -30 °C |
| **Temperature operational max** | 60 °C |
| **Weight** | 100 g |

| | |
|---|---|
| **Number of optional modules** | 2 |
| **Supply voltage ac/dc max** | 30 V |
| **Supply voltage ac/dc min** | 18 V |
| **Diameter** | 70 mm |
| **Nominal current min** | 0.17 A |






















46
Ø 72
Ø6,5
42


136 / 286 / 436
72
Ø54
Ø5,5


136 / 286 / 436
91
Ø6,4
50
72


46
M6
20
42
Ø 72


70
Ø 72


Ø6,5
74
60
82
81


157 / 307 / 457
Ø 72
Ø54
Ø5,5


46
100
Ø5,5
Ø85


150 / 300 / 450
M20
Ø21


150 / 300 / 450
24
54
65


Ø5,50
31
51
100
82
97
81


61
73


74
73


100
Ø 72


46
Ø 72
Ø6.5
42


136 / 286 / 436
72
Ø54
Ø5.5


136 / 286 / 436
91
Ø6.4
50
72


46
M6
20
42
Ø 72


70
Ø 72


Ø6.5
74
60
82
81


157 / 307 / 457
Ø 72
Ø54
Ø5.5